



## Rubber sponge product guide

Product	Dimension	Density	Hardness	Ref.
<b>EPK-8</b>	60mm by 1m by 2m	80 kg ± 15%	7 to 12 dgr.	EPDM sponge ASTM 2A1
<b>EPK-10</b>	60mm by 1m by 2m	110g± 12%	14 to 18 dgr.	EPDM sponge ASTM 2A1
<b>EPK-15</b>	60mm by 1m by 2m	125±12%	16 to 20 dgr.	EPDM sponge ASTM 2A2
<b>EPK-15wh</b>	60mm by 1m by 2m	125kg± 10%	16 to 20 dgr.	White EPDM sponge ASTM 2A2
<b>EPK-17</b>	52mm by 1m by 2m	170kg±15	17 to 20 dgr.	High-density EPDM sponge ASTM 2A2
<b>EPK-18FR</b>	52mm by 1m by 2m	1 kg±10%	15 to 20 dgr.	Flame-retardant EPDM sponge HBF-1
<b>EPK-25FR</b>	35mm by 1m by 1.8m	125 kg± 10%	24 to 30 dgr.	Flame-retardant EPDM sponge HBF-1
<b>EPK-30FR</b>	35mm by 1m by 1.5m	160 kg± 10%	30 to 38 dgr.	Flame-retardant EPDM sponge UL V-0





<b>HERS-20</b>	50mm by 1m by 2m	125 kg± 10%	22 to 27 dgr.	Flame retardant EPDM sponge (Sulfur-free)
<b>CRK-20</b>	52mm by 1m by 2m	130 kg± 10%	18 to 23 dgr.	CR sponge UL HF-1 certified
<b>EPK-12SF</b>	50mm by 1m by 2m	125kg± 10%	13 to 18 dgr.	Sulfur-free EPDM sponge
<b>EPK-16SF</b>	35mm by 1m by 1.8m	170 kg± 10%	17 to 23 dgr.	Sulfur-free EPDM sponge GMW 17408 cert.
<b>EPK-25SF</b>	35mm by 1m by 1.6m	230 kg± 10%	20 to 27 dgr.	Sulfur-free EPDM sponge GMW 17408 cert.
<b>EPK-25SB</b>	35mm by 1m by 1.8m	180 kg± 10%	20 to 25 dgr.	Sulfur-free EPDM – SBR sponge GMW 17408 cert.
<b>EPSO-80</b>	60mm by 1m by 2m	90 kg±10%	No value	Open-celled EPDM
<b>EPSO-100</b>	40mm by 1m by 2m	115 kg± 10%	No value	Open-celled EPDM GMW 17408 cert.
<b>EPSO-110</b>	40mm by 1m by 2m	120 kg ± 10%	No value	Open-celled EPDM GMW 17408 cert.
<b>EPSO-200</b>	30mm by 0.7m by 1.2m	200~ kg± 10%	No value	High-density and open-celled EPDM sponge

cf. density: kg/cubic m, hardness: shore C hardness tester

\*We can supply each grey and beige colored products if there's a customers request

